

# Specification

LCD Size	32"	42"	52"	65"
Aspect Ratio (W:H)	16:9	16:9	16:9	16:9
Active Display Area (HxW)	392 x 698mm	523 x 930mm	648 x 1152mm	804 x 1428mm
LCD Pixel Pitch	0.51075 mm	0.681 mm	0.6 mm	0.744 mm
Protection	4mm tempered glass (UL-1950)	4mm tempered glass (UL-1950)	4mm tempered glass (UL-1950)	4mm tempered glass (UL-1950)
Cabinet Dimensions (HXWxD)	514 x 820 x 120 mm	643 x 1050 x 131 mm	774 x 1278 x 133 mm	919 x1561 x143 mm
Screen Brightness	500 nits	500 nits	500 nits	450 nits
Response Time	6.5ms total typical	6.5ms total typical	6.5ms total typical	6ms total typical
Contrast Ratio	1500:1	2500:1	1500:1	2000:1
Full Viewing Angle	176°(H) / 176°(V)	178°(H) / 178°(V)	176°(H) / 176°(V)	176°(H) / 176°(V)
Colors	16.7 million	16.7 million	16.7 million	16.7 million
Line Voltage	100-240V (50/60Hz)	100-240V (50/60Hz)	100-240V (50/60Hz)	100-240V (50/60Hz)
Power Consumption	135 W	200 W	270 W	550 W
Operating Temperature	0~50°C	0~50°C	0~50°C	0~50°C
Operating Humidity	20~100%	20~100%	20~100%	20~100%
Weight	30kg	40kg	60kg	85kg
Backlight Life	50,000 hours	60,000 hours	50,000 hours	60,000 hours
DDC	DDC 2B	DDC 2B	DDC 2B	DDC 2B
Connectors	VGA input x 1 VGA output x 1 DVI input x 1 RS232 x 1	VGA input x 1 VGA output x 1 DVI input x 1 RS232 x 1	VGA input x 1 VGA output x 1 DVI input x 1 RS232 x 1	VGA input x 1 VGA output x 1 DVI input x 1 RS232 x 1
Built in IPC or SMP	Option	Option	Option	Option

Model Solution	32"	42"	52"	65"
Resolution				
1366 x 768	V			
1920 x 1080		V	V	V